

## **Z20 POS Stand**

For I-Series 4 for Android





Integrated I/O



**Concealed Cable Routing** 



Flip the Display

## **Product Overview**

The Z20 POS Stand delivers elegance to the point-of-sale. Complete with an integrated connectivity hub, concealed cable routing and the flexibility to either flip the main display from full service to self-service or add a fixed customer facing display on the back, the Z20 packs everything you need at the point of sale. Designed to support Elo's Android I-Series 4, the Z20 POS stand includes a universal VESA mount making it easy to install the 10- and 15-inch touchscreens with your choice of Qualcomm or Rockchip processor options.

Start changing the way customers and employees interact by deploying a new generation of interactive point-of-sale technologies that provide seamless integration, effortless provisioning and simplified device management via EloView or your preferred management tools.

The flip stand design seamlessly converts the employee-facing fullservice POS terminal to a customerfacing self-service kiosk

Integrated connectivity hub built into the stand with a compartment for seamless cable routing

Universal VESA mounts allow you to easily attach an employee-facing display and cusotmer-facing display

## **Z20 POS Stand**

Specifications	
Color	Dark Grey Metallic/ Black
	Main Display: 10-inch and 15-inch I-Series 4 for Android
Compatibility	Customer Facing Display:  1002L - Elo P/N: E155834 and E324341  1302L - Elo P/N: E683595 and E683787  1502L - Elo P/N: E125496
I/O Ports	DC input  4 x USB-A 3.0 Port (900mA)  RJ12 (serial/cash drawer)* 12/24V  Ethernet LAN (Gigabit)**  USB-C output - CFD (DisplayPort, Touch and Power Delivery up to 27W)***
	*User will need to select the mode  **Ethernet upload and download speeds will decrease to ~250Mbps when using the CFD  *** USB speeds will be reduced to 2.0 speeds when DP video is being output.
Pre-wired Cables	19VDC (5.5mm) cable to I-Series USB-C cable to connect to I-Series
Hinge Life Rating	5000 flips
Dimensions (W x D x H)	7.6" x 10.0" x 6.7" / 194 mm x 255 mm x 169 mm
Shipping Dimensions	12.2" x 12.6" x 12.6" / 310 mm x 320 mm x 320 mm
Weight	12.8 lbs / 5.8 kg
Shipping Weight	5.9 lbs / 2.7 kg
Temperature	Operating: 32°F to 104°F (0°C to 40°C); Storage: -4°F to 122°F (-20°C to 50°C)
Humidity	Operating: 20%-80%; Storage: 5%-95%
Warranty	2 years standard
Extended Warranty	3 year warranty coverage - Elo P/N: E375367 4 year warranty coverage - Elo P/N: E375573 5 year warranty coverage - Elo P/N: E375771 2 year warranty coverage + AUR - Elo P/N: E375970 3 year warranty coverage + AUR - Elo P/N: E376169 4 year warranty coverage + AUR - Elo P/N: E376362 5 year warranty coverage + AUR - Elo P/N: E376547
Regulatory Approvals	FCC (US); IC (Canada); CE (Europe); VCCI (Japan); RCM (Australia)
What's in the Box	Z20 POS Stand  8 x M4x10 Flat-head Screw (in bag "A")  2 x M4x6 Pan-head Screw (in bag "B")  Screw-height tool Installation Guide  0.3m USB-C to USB-C cable (to provide USB and Video signals to the CFD)  150W Power Brick  North American Power Cable  European Power Cable  Tie Wrap  VESA Cover, Bottom, 15"  VESA Cover, Top, 15"
	VESA Cover, Rottom, 10" VESA Cover, Top, 10" Base Plate – for mounting to a countertop

## **Ordering Information**

Part Number	Color
E809321	Dark Grev Metallic/ Black

Learn more about Elo at **EloTouch.com**.

Americas Europe (EMEA)

 Tel +1 408 597 8000
 Tel +32 16 930 136
 Tel +86 (21) 3329 1385

 elosales.na@elotouch.com
 EMEA.Sales@elotouch.com
 EloAsia@elotouch.com

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo and TouchPro are either trademarks or registered trademarks of Elo Touch Solutions, Inc. Android is a trademark of Google LLC. Google Mobile Services is a trademark of Google LLC. All other trademarks are the property of their respective owners. © 2021 Elo Touch Solutions, Inc. All rights reserved. 21111AES00159

**Asia Pacific** 

