



# 1517L 15-inch LCD

Touchscreen Monitor



**Integrated Touch**



**Commercial Grade**



**3-Year Warranty**

## Product Overview

The Elo 1517L 15-inch standard format touchscreen monitor is built to withstand the rigors of continuous public use with a rugged built-for-touch design. Its stylish, thin and modern look coupled with a retail-focused feature set makes it an attractive solution for commercial touchscreen monitor needs. The 1517L, offered in white or black, is well suited for point-of-sale, point-of-information, point-of-service, interactive signage and loyalty systems.

The touchscreen monitor offers multiple mounting options to ensure installation flexibility including: wall- and pole-mount via standard VESA mount patterns as well as tabletop accommodations with the use of the desktop stand. Capped through-mount holes on the base of the touchmonitor ensure table-top security.

### Available touch technologies:

- AccuTouch® Resistive
- IntelliTouch® SAW

**Customize with an integrated 3-track magnetic stripe reader (MSR)**

**Desktop, wall or VESA mounting**

## 1517L 15-inch LCD Touchscreen Monitor

Specifications	
Model	1517L
Color	Black or White
Active Display Area	11.97" x 8.98" (304.13mm x 228.10mm)
Monitor Dimensions (with stand)	14.10" x 7.76" x 12.57" (358.1mm x 197mm x 319.4mm) (dimensions vary with stand position and options selected)
Monitor Thickness	1.7" (43mm) panel depth
LCD Technology	Active matrix TFT LCD with LED backlighting
Diagonal Size	15.0"
Aspect Ratio	4:3
Native (Optimal) Resolution	1024 x 768
Other Supported Resolutions	640 x 480 @ 60Hz, 75Hz; 720 x 400 @ 70Hz; 800 x 600 @ 56Hz, 60Hz, 75Hz; 1024 x 768 @ 60Hz, 75Hz
Number of Colors	16.2 million
Number of Touches	Single-touch and dual-touch
Brightness (typical)	LCD Panel: 300 nits; AccuTouch: 240 nits; IntelliTouch: 270 nits; IntelliTouch ZB: 270 nits
Response Time - Total (typical)	23 msec
Viewing Angle (typical)	Horizontal: ± 80° or 160° total / Vertical: 70°/80° or 150° total
Contrast Ratio (typical)	800:1
Video	Analog VGA on Female DB-15 connector Digital HDMI on Type A receptacle Input Video Horizontal Sync frequency range: 31.5 - 60KHz Input Video Vertical Sync (frame rate) frequency range: 56-75Hz
Power	Monitor AC input power connector: IEC 60320 C6 Monitor AC input voltage specifications: 100-240VAC, 50/60Hz Monitor DC input power connector: Coaxial power jack (2.0mm pin outer diameter, 6.4mm barrel inner diameter) Monitor DC input voltage specifications: 12VDC +/- 5% Note: Optional AC-DC power adapter sold for this monitor: AC input connector: IEC 60320 C14 AC input voltage specification: 100-240VAC, 50/60Hz Power Consumption (Typical): ON (monitor): 10.5W; SLEEP (monitor): 1.2W; OFF (monitor): 0.4W
Replacement DC Power Supply	The monitor may be powered with DC voltage. A optional 12V DC power brick, Elo P/N: E005277, is available at additional cost.
AC Power Cable	North American & EU power cables included. UK AC power cables included with P/Ns available for EMEA.
Weight (with stand)	Unpackaged: 9.48 lbs (4.3 kg); Packaged: 16.09 lbs (7.3 kg)
Shipping Dimensions	19.17" x 9.09" x 19.09" (487mm x 231mm x 485mm)
Mounting Options	75 mm VESA mount, capped through-mount holes
On-Screen Display (OSD)	Controls: Menu, Up, Down, Select Settings: Brightness, Contrast, Clock, Phase, H- position, V-Position, Auto-Adjust, Aspect Ratio, Sharpness, Color Temperature, OSD Timeout, OSD Language, Recall Defaults Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese Lockouts: OSD, Power
Temperature	Operating: 0 °C to 40 °C / 32 °F to 104 °F; Storage: -20 °C to 60 °C / -4 °F to 140 °F
Humidity (non-condensing)	Operating: 20%-80%; Storage: 10%-95%
Regulatory Approvals and Declarations	Argentina S-mark, Australia RCM, Canada cUL, IC, China CCC, Europe CE, United Kingdom UKCA, Japan VCCI, Korea KCC, e-Standby, Mexico NOM, Taiwan BSMI Mark, United States UL, FCC, International CB, RoHS, China RoHS, WEEE
Warranty	3 years standard
Extended Warranty Options	4 year warranty coverage - Elo P/N: E898247 5 year warranty coverage - Elo P/N: E898449 3 year warranty coverage + AUR - Elo P/N: E898648 4 year warranty coverage + AUR - Elo P/N: E894921 5 year warranty coverage + AUR - Elo P/N: E895125
MTBF	50,000 hours demonstrated
What's in the Box	Quick Install Guide, VGA Cable (DB-15 male to DB-15 male), Touch USB Cable (USB Type A plug to USB Type B plug), power cable, IEC 60320-C5 to NA/EU plug, Stand Base assembly, Filler Plate, HDMI cable

## Ordering Information

Model	Part Number	Technology	Interface	Bezel	Surface Treatment
1517L	E523163	AccuTouch	Serial/USB	Yes	Antiglare
	E144246	AccuTouch ZB	Serial/USB	No	Antiglare
	E344758	IntelliTouch	Serial/USB	Yes	Antiglare
	E829550	IntelliTouch ZB	Serial/USB	No	Clear
	E273226	IntelliTouch ZB	Serial/USB	No	Antiglare

Learn more about Elo at [EloTouch.com](http://EloTouch.com).

### Americas

Tel +1 408 597 8000  
elosales.na@elotouch.com

### Europe (EMEA)

Tel +32 16 930 136  
EMEA.Sales@elotouch.com

### Asia Pacific

Tel +86 (21) 3329 1385  
Elo.Asia@elotouch.com

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo, AccuTouch and IntelliTouch are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2021 Elo Touch Solutions, Inc. All rights reserved. 21071AES00011

