

# Gainscha

Reliable and Innovative



## **SURPASS SERIES** - Desktop Thermal Transfer Barcode Printer **4" Wide GS-2406T**

POWERFUL, HIGH PERFORMANCE, AFFORDABLE



### KEY FEATURES

- 152.4mm (6") per second print speed for 203 DPI.
- 127mm (5") per second print speed for 300 DPI.
- 400 MHz 32-bit ARM9 processor with 64 MB SDRAM, 32 MB Flash memory or 64 MB SDRAM, 128 MB Flash memory.
- Internally scalable true type font engine.
- USB Host for scanner or PC keyboard.
- Firmware emulates EPL, ZPL, ZPL II, DPL, TSPL.
- BarTender Free Windows® drivers and label design software (available via download).
- Provide Windows printer utility, Windows SDK and Android SDK.
- Solution for retail POS, shelf labeling, product marking, healthcare patient safety, inventory management, shipping, high resolution print barcodes and graphics, food ingredient marking, office applications.

# SURPASS SERIES -

## 4" Desktop Thermal Transfer Barcode Printer

PRINTER MODEL	GS-2406T	GS-3405T
Resolution	8dots/mm (203DPI)	12dots/mm (300DPI)
Printing Method	Thermal Transfer & Direct Thermal	
Max. print speed	152.4mm (6")/second	127mm (5")/second
Max. print width	104mm (4.1")	108.4mm (4.27")
Max. print length	2,794mm (110")	1,016mm (40")
CPU	400MHZ, 32-bits, ARM9	
Memory RAM	64MB SDRAM	
Memory ROM	32MB Flash Memory(128MB Flash Memory Option)	
Interface	USB 2.0 High Speed 480Mbps USB Host 2.0, for scanner or PC keyboard RS-232 Internal Ethernet 10/100Mbps Internal Bluetooth 4.0 (factory option) Internal Wi-Fi (factory option)	
Dealer options	Guillotine cutter • peeler	
Sensors	Head open sensor, Ribbon end sensor, Reflective sensor (moveable), Transmissive sensor (moveable)	
Power	External universal switching power supply Input: AC 100-240V, 2.5A, 50-60Hz, Output: DC 24V, 2.5A, 60W	
User Interface	1 power switch, 2 buttons (Feed & Pause), 3 LEDs (Online, Error, Ribbon status)	
Internal fonts	8 alpha-numeric bitmap fonts True type font engine (need download scalable font file)	
1D Barcode	Code 11, Code 39, Code 93, Code 128 (subsets A, B, C), UPC-A, UPC-E, UCC-128, Codabar,EAN/JAN-8, EAN/JAN-13, Interleaved 2 of 5, ITF14, MSI Pleassy, PostCode, Telepen	
2D Barcode	QR Code, Micro QR Code, PDF417, Micro PDF417, Grid Matrix, MaxiCode, Aztec Code, Data Matrix	
Rotation	Font and barcode support 0, 90, 180, 270 degree	
Printer language	Compatible to EPL, ZPL, ZPL II, DPL, TSPL	
Ribbon	300 M long, max. OD 67mm, 1" core (ink coated outside)	
Ribbon width	30mm~110mm (1.18"~4.33")	
Media type	Continuous, die-cut, black mark, fan-fold, notched (outside wound)	
Media width	20~118mm (0.7"~4.6")	
Media thickness	0.055~0.254mm (2.17~10mil)	
Media core diameter	25.4mm (1")	
Label roll capacity	127mm (5")OD	
Label length	5~2,794mm (0.2"~110")	5~1,016mm (0.2"~40")
Physical dimension	280mm(D) x 200mm(W) x 182mm(H)	
Weight	2.09kg	



### Enclosure

ABS plastic

### Certification

FCC, CE, CCC, BIS, CB

### Environment condition

Operation: 5~40°C, 25~85% non-condensing  
Storage: -40~60°C, 10~90% non-condensing

### Environment concern

Comply with RoHS, REACH, WEEE

### Accessories

Windows labeling software CD disk/Quick start guide/USB cable/Power cord External universal switching power supply/1" ribbon spindle x 2 for 300M ribbon

### Limited warranty

Printer: 2 years  
Print head: 25km (1 million inches)/12 months  
Roller: 50km (2 million inches)/12 months

### User options

External roll mount

### Gainscha Auto ID Co., Ltd.

Add: Zone G, 2nd floor, Workshop No. 1, No. 15 pingbei  
2nd Road, Xiangzhou District, Zhuhai

Tel : +86 756 3965698  
Fax : +86 756 3965694  
E-mail : sales@gainscha.com  
Website: gainscha.com.tw | gainscha-aidc.com