



D4 202

Label Printer

D4 202 is a compact size 4" desktop label printer with a industrial level equipments and high performance. D4 202 is equipped with a colorful backlight LCD with clear image display that makes the menu friendly to users. Multiple communication ports, SD slot for the data storage, real time clock for time and date printing application are some of the main features that makes this label printer ideal for all range of application. Two models available D4 202 and D4 202 ETH with Ethernet interface on board.



TECHNICAL SHEET

	D4 202	D4 202 ETH
Printing Method		Direct thermal / Thermal transfer
Resolution		203 dpi
Printing speed		5 ips
Print Width		104 mm
Sensors		Moveable see-through and reflective sensor Ribbon sensor Cover open sensor
RAM Memory		128 MB
Display		Colorful 2.8" backlight LCD display, 240 × 320 dots
Control Panel		4 multi-functional keys
Media		Maximum label width: 110 mm Minimum label width: 15 mm Maximum roll diameter: 127 mm Core diameter: 25.4 mm Media thickness: 0.06 mm to 0.2 mm Media type: Continuous, die-cut, tag, fan-fold, black mark
Ribbon		OD: 39 mm Max length: 100 m Width: 25.4 mm to 110 mm ID: 12.7 mm Ribbon type: Wax, wax/resin, resin
Emulation Language		PEPL, PDPL, PZPL
Interfaces	USB port USB master port Serial port Ethernet port 10/100Mbps (optional)	USB port USB master port Serial port Ethernet port 10/100Mbps on board
Supported 1D/2D Barcodes		Code39 stand or extended, Code39 with check digit, Code93, Code128 UCC, Code128 Auto A,B,C mode, EAN8, EAN8/13 2&5 digit add-on, EAN13, Interleaved 2 of 5, Interleaved 2 of 5 with check digit, Interleaved with human readable check digit, UCC/EAN 128, UPC-A, UPC-A 2&5 digit add-on, UPC-E, UPC-E 2&5 digit add-on, UPC Interleaved 2 of 5, Code 11 PDF417, Maxicode, Data Matrix, QR code
Fonts		5 internal expandable bitmap fonts (alpha-numeric) 2 internal expandable bitmap fonts (numeric only) Downloadable soft font 4 directions: 0, 90, 180, 270 degrees
Image		PEPL: PCX, Direct binary graphic
Options		Peeler kit Cutter Ethernet module
Power		Switching power adapter Input: 100 to 240 V, 1.8 A, 50~60 Hz Output: 24 V, 2.5 A
Audio		Beep sound when error occurs
Environment		Operation: 5 °C to 45°C Storage: -20 °C to 50 °C
Humidity		Operation: 0% to 90% non condensing Storage: 5% to 95% non condensing
Dimensions		263 mm (L) × 200 mm (W) × 188 mm (H)

D4 202

D4 202 ETH

Weight

2 kg

MODELS



911MK020100333

LABEL PRINTER D4 202 USB
RS232 WITH DISPLAY BLACK



911MK020100733

LABEL PRINTER D4 202 ETH USB
RS232 WITH DISPLAY BLACK

Via Berettine, 2 - 43010 Fontevivo PR - VAT: IT02498250345 - TEL: +39 0521 680111 - FAX: +39 0521 610701 - UNIQUE CODE: 8RQN7AZ

The technical data on this website are not binding and may be changed without advanced notice.

Last update: 07 October 2024