

WEIGHT ONLY OR  
PRICE COMPUTING SCALE

CHECKOUT SCALE

# DPOS-400 series

scales without  
printer  
02



## Dimensions

DATA IN mm

A	50
B	275
C	65
D	345
E	420*
F	45




Plate dimensions: L300 x W230 mm.  
Weight with packaging: 5.0 kg.

\* + 9.2 mm with glass plate and legs adjusted in height to the minimum.



LCD  
SEGMENT  
DISPLAY



RS-232



USB



METROLOGICAL  
VERIFICATION  
OPTIONAL (EU)

## Models

### Flat Format

	Vendor Display	Buyer Display	Communication protocols	Power through a USB	Capacity / Accuracy	Reference
DPOS-400 F - 1 DISP.	LCD Graphic	-	Up to 100	Mains / Others	6 kg / 2 g - 15 kg / 5 g	7POSP00LNE__
DPOS-400 F - 2 DISP.	LCD Graphic	LCD Graphic	Up to 100	Mains / Others	6 kg / 2 g - 15 kg / 5 g	7POSPP0LNE__

### Pole Format

	Vendor Display	Buyer Display	Communication protocols	Power through a USB	Capacity / Accuracy	Reference
DPOS-400 P - 1 DISP.	LCD Graphic	-	Up to 100	Mains / Others	6 kg / 2 g - 15 kg / 5 g	7POST00LNE__
DPOS-400 P - 2 DISP.	LCD Graphic	LCD Graphic	Up to 100	Mains / Others	6 kg / 2 g - 15 kg / 5 g	7POSTT0LNE__
DPOS-400 P - 2 DISP. <i>(1 in base and 1 in pole)</i>	LCD Graphic	LCD Graphic	Up to 100	Mains / Others	6 kg / 2 g - 15 kg / 5 g	7POSPT0LNE__

# Characteristics and functionality

## Main characteristics

- Weight only or price computing scale for checkout applications.
- Modular and modern design.
- Easy integration into counters.
- Additional tempered glass plate available. Customizable with client's logo.
- Valid for legal metrology.

## Features

- EAN heading programming (according to the communication protocol).
- Tare, fix tare and manual zero.
- Display of price in a secondary currency.
- Energy saving via programmable on and off back lighting switching and automatic disconnection.
- Power supply and communications through one single USB cable.

## Capacity / Accuracy

- Multi-range (3,000 divisions): 6 kg / 2 g - 15 kg / 5 g.
- Optional:
  - Mono-range (3,000 divisions): 15 kg / 5 g.

## Available formats

- Flat.
- Pole.

## Construction

- Structure:
  - ABS plastic casing.

- Display:
  - Easy to install in multiple positions (1 or 2 displays).
  - Backlit LCD matrix graphic display.
  - 5 digits (up to H20 mm) per display.
  - Shows only weight or weight, price/kg and total (connected to POS and depending on the communication protocol).
- Keypad with 3-keys.
- Plate:
  - Type: Flat.
  - Material: Stainless steel. Also available in tempered glass (additional).

## Communication to PC / POS / ECR

- RS-232 interface.
- USB.
- Communication protocols available for the main POS and ECR in the market.
- Multi-protocol: communication protocol is selected in the scale (40 protocols available). More protocols can be added from PC by telecharge (maximum: 60 protocols more).
- "OPOS" driver.

## Power supply

- Mains: power via USB connection, with an AC/DC adapter from 110/240 VAC to 5 V / 500 mA.
- Others: other sources through a USB connection for example with a PC.

## Energy consumption

- 1 W (approx.).

# Options

Option	Characteristics	Reference
Capacity 15 kg / 5 g	Mono-range (3,000 divisions).	...N __ (*)
Metrological verification (M)	According to EU weighing directives. (See section on equipment metrological verification).	Consult

(\*) The scale references with this capacity are obtained by replacing the last characters of the reference for the standard scale with the indicated ending.

# Accessories

## Tempered glass plate (customizable)

Stainless steel plate also included.



Ref: 494839A

Note:

- The references correspond to standard models: Black ABS plastic casing, backlit LCD segment display, flat stainless steel plate and RS-232 and USB communications. Capacity/Accuracy: 6 kg / 2 g - 15 kg / 5 g.