

0704LS 7-inch LCD

Touchscreen Monitor





Optically-bonded display



Ultra-thin design



Low blue light & Flicker free

Product Overview

The Elo 0704LS 7-inch HD touchscreen monitor delivers commercial-grade durability, brilliant display clarity with state-of-the-art optical bonding and a minimalistic design perfect for any application. Backed by a three-year warranty, the 0704LS offers an energy efficient TouchPro® PCAP touchscreen enabling up to 10 simultaneous touches. With a clean design aesthetic, dual built-in speakers, flexible mounting options and increased viewing comfort with low blue light and flicker free features, the 0704LS touchscreen is well-suited for POS, HMI, interactive digital signage and self-service.

USB-C interface that provides touch, video and power connectivity

Durable IK07 design with chemicallystrengthened scratch resistant glass

Narrow border touchscreen with edge-to-edge glass

0704LS 7-inch LCD Touchscreen Monitor

Specifications				
Color	Dark gray			
Diagonal Size	7"/177.8 mm			
Active Touch Area	5.90" x 3.69" / 149.76 mm x 93.60 mm			
LCD Technology	Active matrix TFT LCD			
Touch Technology	TouchPro PCAP			
Number of Touches	10 Touches			
Aspect Ratio	16:10			
Native Resolution	1280 × 800			
Preset Video Timings	1280 x 800 60Hz; 280 x 800 60Hz RB; 1280 x 720 60hz; 1024 x 768 60Hz; 800 x 600 60Hz; 800 x 500 60Hz; 640 x 480 60Hz			
Number of Colors	16.7M			
Brightness (typical)	Panel: 400 nits; with TouchPro PCAP: 360 nits			
Response Time (Tr + Tf) (typical)	35 msec			
Viewing Angle (typical)	Horizontal: 88°/88° or 176° total; Vertical: 88°/88° or 176° total			
Contrast Ratio (typical)	800:1			
	Accessible through touch OSD, and press Menu button to pop up touch OSD diagram.\			
	Controls: Menu, Power			
On-Screen Display (OSD)	Settings: Brightness, Contrast, Aspect Ratio, Sharpness, Color Temperature, Low Blue Light, OSD Timeout, OSD Language, Touch on Sleep mode, Power LED, Touch Through, Recall Defaults			
	Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese Lockouts: OSD, Power			
I/O Ports	USB Type-C connector			
USB Type-C connector Video Input Video Horizontal Sync frequency range: 30 – 60KHz Input Video Vertical Sync (frame rate) frequency range: 60Hz				
Power	Power Delivery compatible via USB Type-C connector, Input range: (5V±5% 3A/9V±5% 3A/15V±5% 1.8A/20V±5% 1.35A) ON (Default - 100% Brightness): 4.8W SLEEP: 0.8 W OFF: 0.15 W			
Dimensions with Stand (H x W x D)	6.81" x 4.78" x 0.57" / 173.06 mm x 121.56 mm x 14.6 mm			
Shipping Dimensions	9.13" x 6.61" x 2.80" / 232 mm x 168 mm x 71mm			
Weight	Unpackaged: 0.71 lbs / 0.32 kg Packaged: 1.48 lbs / 0.67 kg			
Mounting Options	VESA via 4-hold 75mm mounting adapter on rear of unit.			
Temperature	Operating: 0° C to 40° C / 32°F to 104°F; Storage: -20° C to 60° C / -4°F to 140°F			
Humidity (non-condensing)	Operating: 20% - 80% / Storage: 10% - 95% (38.7° C max wet bulb temperature)			
Regulatory approvals and declarations	Canada CUL, IC; Europe CE; Korea KCC; Taiwan BSMI; United States FCC, UL; Japan VCCI; International CB; Australia RCM; RoHS, China RoHS, WEEE REACH; United Kingdom UKCA			
Impact Protection	IKO7			
Other Features	TUV Rhineland (Low Blue Light) TUV Rhineland (Flicker Free) Power collection function via DDCCI			
Warranty	3 years			
MTBF	50,000 hours demonstrated			
Extended Warranty Option	4 year warranty coverage - Elo P/N: E898247 5 year warranty coverage - Elo P/N: E898449			
Box Content	0704LS Touch monitor Quick Install Guide USB Type-C cable			

Ordering Information

Part Number	Technology	Surface Treatment	Touch Interface	Color
E967730	TouchPro PCAP	Anti-glare	LISB	Dark Gray

Learn more about Elo at **EloTouch.com**.

Americas Europe (EMEA) Asia Pacific

 Tel +1 408 597 8000
 Tel +32 16 930 136
 Tel +86 (21) 3329 1385

 elosales.na@elotouch.com
 EMEA.Sales@elotouch.com
 Elo.Asia@elotouch.com

