

# K180

## Wireless Barcode Scanner

### Precision Scanning, Effortless Decoding

Equipped with a professional scan engine for millisecond decoding, effortlessly scans 1D/2D barcodes, including damaged, distorted, laminated, screen, and low-contrast barcodes.

### Elegant and Outstanding, Lightweight and Effortless

The whale-shaped curved design combined with a compact and exquisite form ensures an easy grip, smooth handling, and comfort during extended use.

### Wireless Freedom, Seamless Connectivity

Supports Bluetooth 5.2 for seamless pairing with smartphones, tablets, notebooks, and desktops, ensuring broad compatibility and effortless integration into your existing workflow.

### Triple Scan Feedback for Enhanced Usability

Real-time scanning feedback via vibration motor, buzzer, and LED indicator. Flexible feedback ensures clear, accurate responses in any retail environment, preventing missed scans.

### Long-Lasting Battery Power

Powered by a 2500mAh battery, offering over 30,000 scans on a full charge. Enjoy prolonged operations and reduced downtime, maximizing productivity with fewer recharges needed.

### Hands-Free Scanning, Charging Simultaneously

Equipped with a charging cradle and auto-sensing mode, it frees your hands for effortless operation while meeting high-frequency scanning and long battery life needs.



# K180 Wireless Barcode Scanner

## Specifications



### Image Sensor

1280\*1080 CMOS  
60 frames per second



### Illumination

White LED



### Aimer

650nm laser  
red crosshair



### Resolution

≥3mil



### Scanning Feedback

Vibration motor, buzzer,  
and LED indicator



### Scan Angle

Roll 360°  
Pitch ±60°  
Skew ±60°



### Communication Modes

Synchronous mode  
Asynchronous mode  
Batch mode



### Dimensions

138.5mm\*42.3mm\*36.9mm  
Weight: 95g



### Wireless Connectivity

Bluetooth 5.2  
Radio range: 80m  
(direct line of sight in open air)  
\*Data from UROVO Lab



### Battery

2500mAh



### Environmental

Operating temperature: 0~50° C  
Storage temperature: -40~70° C  
Humidity: 5%~95%(non-condensing)  
Ambient light immunity: 0~100000 LUX  
ESD: ±15kV air discharge, ±8kV direct  
discharge



### Decode Capabilities

1D: UPC-A, UPC-E, EAN-8, EAN-13, ISBN,  
Code 128, GS1 128, ISBT 128, Code 39, Code93,  
Code 11, Interleaved 2 of 5, Industrial 2 of 5, Matrix 25,  
Standard 25, Codabar, MSI/MSI PLESSEY, GS1  
DataBar etc.

2D: QR Code, PDF417, DataMatrix (ECC200), Micro  
QR, Hanxin Code, Maxi Code, Aztec etc.

#### UROVO PTE. LIMITED

Website: en.urovo.com

Email: urovo@urovo.com

Address: 1 Raffles Place, #21-01 One Raffles Place Tower 1,  
Singapore 048616

#### Urovo Europe

Website: europe.urovo.com

Email: sales-europe@urovo-emea.com

Address: de Maas 9, 5684PL, Best, the Netherlands

#### Urovo North America

Website: us.urovo.com

Email: urovo@urovo.com

Address: 1990 Main Street, Suite 750, Sarasota,  
Florida 34236

**\*This page is subject to change  
without prior notice**