Smart Payment Terminal


SUNMI P3 AIR

Convenience in hand,



SUNMI DMP

SUNTER SECUTION







Lightweight power in your hand

313g body + slim 15.9mm profile,Lightweight design, comfortable even during long use.

Professional performance in your hand

Qualcomm octa-core 2.4 GHz processor, Up to 8 GB RAM + 128 GB ROM, effortlessly handling diverse business needs.

Seamless payment in your hand

Dual-sided NFC readers, tap to pay with ease.





Supports multiple payment methods









Certified for secure payments across all channels













SUNMI P3 AIR Application Scenario



Restaurant



Retail



Takeout



Delivery

SUNMI P3 AIR Tech Specs

Product Model

T6F0A(Standard version) T6F0B(Scanner version)

Security Model

T6F0

CPU

Octa-core, up to 2.4GHz

os

SUNMI OS (Based on Android 13)

Memory

4GB RAM + 64GB ROM 8GB RAM + 128GB ROM (Optional) Extended Micro SD Card Slot Up to 256GB

Displays

6.75" HD+, 720*1600 Pixels, IPS Capacitive Multi-touch Screen, Anti-fingerprint Coating

Buttons

1*Power button (Fingerprint ID optional) 1*Volume button 2*Function button

Card Slots

1*Nano SIM + 1*Micro SD + 2*PSAM 2*Nano SIM + 2*PSAM (Optional)

eSIM

Supported (Optional)
*eSIM will replace 1 SIM in
2 SIM case

Ports

1*Type-C 2*Pogo PIN at the bottom for charging 8*Pogo PIN on the back for connecting accessories (Optional)

Cellular

4G/3G/2G

Wi-Fi

5GHz/2.4GHz IEEE 802.11 a/b/g/n/ac

Hyper Wi-Fi

Supported (Optional)

Bluetooth

Bluetooth 5.1, Support BLE

Positioning

GPS/Glonass/Beidou/Galileo

Cameras

5MP FF Front Camera+ 13MP AF Rear Camera

Scanner

Professional 2D Scan Engine (Optional)

Magstripe Reader

Support 1/2/3 track, Bi-direction, comply with ISO 7810/7811 standards

IC Card Reader

Support smart IC card, comply with ISO 7816 standard

NFC

Tap on screen Support ISO/IEC 14443 TypeA/B, Mifare, Felica, ISO 15693 compliant

Audio

1*Speaker 1*Microphone

Battery

Removable Lithium Polymer Battery, 3.87V/5000mAh

Sensors

Light sensor Proximity sensor

Power Adapter

Input: 100V-240V AC Output: 9V2A/5V2A DC

Dimensions(L*W*H)

181.5*79.9*15.9 mm

Net Weight

313g(Including battery)

Protection

P65

Environment

Operating temperature: -10°C-50°C Storage temperature: -20°C-70°C Operating Humidity: 5%-95% non-condensing

Accessories (Optional)

Protective Film/Protective Case/Charging Cradle/Hand Strap/Battery Charging Cradle

Certifications

PCI PTS 6.x, EMV L1 & L2, EMV Contactless L1, Visa payWave, MasterCard PayPass, UPI Quickpass, Amex ExpressPay, Discover D-PAS, JCB, TQM, FCC, ISED, CE, CB, ROHS, WEEE, REACH